



Remo

FEATURES

Meets safety and performance standards of ANSI/BIFMA x 5.1-2011

- High back version has height and pivoting adjustable mesh headrest.
- Breathable knitted mesh back moves with the user providing flexible continuous support with air flow.
- Mesh back is stretched over a nylon reinforced with fiberglass frame.
- Standard with adjustable lumbar support.
- Seat is fully upholstered with and padded with CFC free high-resiliency polyurethane foam, a waterfall front edge design to alleviate pressure form the back of the thighs.
- Back angle adjustment with back tension adjustment.
- 3" (75 mm) height adjustable arms, with SPA, Swivel Pivot Arm pad.
- The seat swivel and height adjustment is obtained by a 3" (75 mm) pneumatic gas cylinder.
- Black nylon 5 star base.
- Casters, VTW, carpet-twin wheel casters.



5251

High-Back



5252

Mid-Back

Max Height:	43.5-48.5"	1105-1230 mm	39.5-42.5"	1005-1080 mm
Max Width:	26.75"	680 mm	26.75"	680 mm
Max Depth:	27"	685 mm	27"	685 mm
Arm Height:	24-27"	610-685 mm	24-27"	610-685 mm
Back Height:	27-29"	685-735 mm	22-24"	560-610 mm
Seat Height:	16.5-20"	420-510 mm	16.5-20"	420-510 mm
Seat Width:	19"	485 mm	19"	485 mm
Seat Depth:	16.5-20.5"	420-520 mm	16.5-20.5"	420-520 mm
Wt/Chair:	47 lbs.	21 kg	44 lbs.	20 kg
Volume:	19 ft³	0.54 m³	19 ft³	0.54 m³
COM Fabric:	0.8 yd	0.7 m	0.8 yd	0.7 m
Per Carton:	2		2	

Remo



R e m o